



# UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE  
United States Patent and Trademark Office  
Address: COMMISSIONER FOR PATENTS  
P.O. Box 1450  
Alexandria, Virginia 22313-1450  
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/624,257	07/21/2003	Leonard N. Schiff	020575	7349

23696 7590 11/03/2006  
QUALCOMM INCORPORATED  
5775 MOREHOUSE DR.  
SAN DIEGO, CA 92121

EXAMINER

SAFAIPOUR, BOBBAK

ART UNIT PAPER NUMBER

2618

DATE MAILED: 11/03/2006

Please find below and/or attached an Office communication concerning this application or proceeding.

<b>Office Action Summary</b>	<b>Application No.</b> 10/624,257	<b>Applicant(s)</b> SCHIFF ET AL.	
	<b>Examiner</b> Bobbak Safaipour	<b>Art Unit</b> 2618	

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

#### Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

#### Status

- 1) ☒ Responsive to communication(s) filed on 21 July 2003.
- 2a) ☐ This action is **FINAL**.                      2b) ☒ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

#### Disposition of Claims

- 4) ☒ Claim(s) 1-30 is/are pending in the application.
- 4a) Of the above claim(s) \_\_\_\_\_ is/are withdrawn from consideration.
- 5) ☐ Claim(s) \_\_\_\_\_ is/are allowed.
- 6) ☒ Claim(s) 1-30 is/are rejected.
- 7) ☐ Claim(s) \_\_\_\_\_ is/are objected to.
- 8) ☐ Claim(s) \_\_\_\_\_ are subject to restriction and/or election requirement.

#### Application Papers

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☒ The drawing(s) filed on 21 July 2003 is/are: a) ☒ accepted or b) ☐ objected to by the Examiner.  
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).  
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

#### Priority under 35 U.S.C. § 119

- 12) ☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☐ All    b) ☐ Some    \* c) ☐ None of:
1. ☐ Certified copies of the priority documents have been received.
2. ☐ Certified copies of the priority documents have been received in Application No. \_\_\_\_\_.
3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).
- \* See the attached detailed Office action for a list of the certified copies not received.

#### Attachment(s)

- |  |   |
|--|---|
| 1) <input checked="" type="checkbox"/> Notice of References Cited (PTO-892)                                | 4) <input type="checkbox"/> Interview Summary (PTO-413)<br>Paper No(s)/Mail Date. _____ |
| 2) <input type="checkbox"/> Notice of Draftsperson's Patent Drawing Review (PTO-948)                       | 5) <input type="checkbox"/> Notice of Informal Patent Application                       |
| 3) <input type="checkbox"/> Information Disclosure Statement(s) (PTO/SB/08)<br>Paper No(s)/Mail Date _____ | 6) <input type="checkbox"/> Other: _____  |

**DETAILED ACTION**

1. Applicant's claim for domestic priority under 35 U.S.C. 119(e) is acknowledged.

***Claim Rejections - 35 USC § 102***

2. The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

A person shall be entitled to a patent unless –

(b) the invention was patented or described in a printed publication in this or a foreign country or in public use or on sale in this country, more than one year prior to the date of application for patent in the United States.

3. **Claim 24** is rejected under 35 U.S.C. 102(b) as being anticipated by **Rouffet et al (United States Patent #5,410,731)**.

Consider **claim 24**, Rouffet et al show and disclose a method for configuring  $m$  primary satellites to project  $N/m$  beams onto and across an area in a loosely-packed array manner to collectively create  $N$  beam spots to cover the area, with each sub-area covered by a beam spot separated from another sub-area covered by another beam spot by one beam width,  $m$  being an integer greater than 1 and configuring each of the  $m$  primary satellites to facilitate communication over 1 of  $m$  band of frequencies on one beam (figs. 1 and 2; col. 3, lines 5-20; col. 4, lines 60-65; col. 5, lines 4-14; Geostationary satellites S1 and S2 having two coverage areas T1 and T2 on two distinct accesses each being capable of subsequently retransmitting two distinct beams, wherein antenna 1 of satellite S1 retransmitting a beam F1 to the area T1 of the Earth, and a beam F2 to the area T2 of the Earth and antenna 2 of satellite S2 retransmitting a beam F'1 to the area T1, and a beam F'2 to the area T2. A third satellite S3 identical to the satellites S1 and S2 already in orbit, which is fed with a wave E3 by a transmission antenna 21 on the Earth and is capable of retransmitting two beams F''1 and F''2 towards area T1 and T2.

Art Unit: 2618

Furthermore, beam F1 will carry two transmission channels to area T1, beam F2 will carry three transmission channels to area T2, beam F'1 will carry three transmission channels to area T1, and beam F'2 will carry two transmission channels to area T2.).

***Claim Rejections - 35 USC § 103***

4. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

5. The factual inquiries set forth in *Graham v. John Deere Co.*, 383 U.S. 1, 148 USPQ 459 (1966), that are applied for establishing a background for determining obviousness under 35 U.S.C. 103(a) are summarized as follows:

1. Determining the scope and contents of the prior art.
2. Ascertaining the differences between the prior art and the claims at issue.
3. Resolving the level of ordinary skill in the pertinent art.
4. Considering objective evidence present in the application indicating obviousness or nonobviousness.

This application currently names joint inventors. In considering patentability of the claims under 35 U.S.C. 103(a), the examiner presumes that the subject matter of the various claims was commonly owned at the time any inventions covered therein were made absent any evidence to the contrary. Applicant is advised of the obligation under 37 CFR 1.56 to point out the inventor and invention dates of each claim that was not commonly owned at the time a later invention was made in order for the examiner to consider the applicability of 35 U.S.C. 103(c) and potential 35 U.S.C. 102(e), (f) or (g) prior art under 35 U.S.C. 103(a).

5. **Claims 1-10, 12-14, 18-21, and 25-30 are rejected under 35 U.S.C. 103(a) as being unpatentable over Rouffet et al (United States Patent #5,410,731) in view of Farrell (European Patent Application EP 1 065 806 A2).**

Consider **claim 1**, Rouffet et show and disclose a satellite communication system comprising  $m$  primary satellites, each equipped to project  $N/m$  beams onto an area, to collectively create  $N$  beam spots to cover the area,  $m$  being an integer greater than 1 (figs. 1 and 2; col. 3, lines 5-20; col. 4, lines 60-65; Geostationary satellites S1 and S2 having two coverage areas T1 and T2 on two distinct accesses each being capable of subsequently retransmitting two distinct beams, wherein antenna 1 of satellite S1 retransmitting a beam F1 to the area T1 of the Earth, and a beam F2 to the area T2 of the Earth and antenna 2 of satellite S2 retransmitting a beam F'1 to the area T1, and a beam F'2 to the area T2. A third satellite S3 identical to the satellites S1 and S2 already in orbit, which is fed with a wave E3 by a transmission antenna 21 on the Earth and is capable of retransmitting two beams F''1 and F''2 towards area T1 and T2.).

Rouffet et al fail to disclose  $n$  back up satellites, each equipped to project  $N/m$  beams onto the area, to enable each of the  $n$  back up satellites to be able to replace any one of the  $m$  primary satellites on demand,  $n$  being an integer equal to or greater than 1.

However, Farrell shows and discloses as known in the art a universal replacement communications satellite designed for orbiting the Earth in a geostationary orbit which emulates the communications performance of a substantial percentage of existing geostationary communication satellites and therefore for which it can be a replacement (col. 3, lines 40-55).

Therefore, it would have been obvious of one of ordinary skill in the art to incorporate the teachings of Farrell into the system of Rouffet et al to have a practical but satisfactory replacement satellite that can emulate the performance of the main or primary satellites while still being technologically, economically, and other practicable.

Consider **claim 2**, and **as applied to claim 1 above**, Rouffet et al show and disclose the claimed invention wherein said  $m$  primary satellites are equipped to project  $N/m$  beams onto and across an area in a loosely-packed array manner, with sub-areas covered by a beam spot separated from other sub-areas covered by another beam spot by one beam width, and each equipped to facilitate communication over 1 of  $m$  band of frequencies on one beam (figs. 1 and 2; col. 3, lines 5-20; col. 4, lines 60-65; col. 5, lines 4-14; Geostationary satellites S1 and S2 having two coverage areas T1 and T2 on two distinct accesses each being capable of subsequently retransmitting two distinct beams, wherein antenna 1 of satellite S1 retransmitting a beam F1 to the area T1 of the Earth, and a beam F2 to the area T2 of the Earth and antenna 2 of satellite S2 retransmitting a beam F'1 to the area T1, and a beam F'2 to the area T2. A third satellite S3 identical to the satellites S1 and S2 already in orbit, which is fed with a wave E3 by a transmission antenna 21 on the Earth and is capable of retransmitting two beams F''1 and F''2 towards area T1 and T2. Furthermore, beam F1 will carry two transmission channels to area T1, beam F2 will carry three transmission channels to area T2, beam F'1 will carry three transmission channels to area T1, and beam F'2 will carry two transmission channels to area T2.).

Rouffet et al fail to disclose except for said  $n$  back up satellites are also equipped to project  $N/m$  beams onto and across the area in a loosely-packed array manner, with each sub-area

Art Unit: 2618

covered by a beam spot separated from another sub-area covered by another beam spot by one beam width, and each equipped to facilitate communication over 1 of  $m$  band of frequencies on one beam.

However, Farrell shows and discloses as known in the art a universal replacement communications satellite designed for orbiting the Earth in a geostationary orbit which emulates the communications performance of a substantial percentage of existing geostationary communication satellites and therefore for which it can be a replacement (col. 3, lines 40-55). Furthermore, Farrell discloses that the replacement satellite comprises two or more Ku and 2 or more C band downlink antennas, each antenna capable of outputting a downlink beam comprising downlink Ku and C band signals, respectively, with each downlink beam being separately directable to different locations on Earth (col. 4, lines 14-19 and 33-37). The replacement satellite will be designed for the same uplink and downlink frequency plans and telemetry and command subsystem frequencies (col. 2, lines 22-26).

Therefore, it would have been obvious of one of ordinary skill in the art to incorporate the teachings of Farrell into the system of Rouffet et al to have a practical but satisfactory replacement satellite that can emulate the performance of the main or primary satellites while still being technologically, economically, and other practicable.

Consider **claim 3**, and **as applied to claim 1 above**, Rouffet et al further disclose 3 primary satellites (fig. 3; col. 4, lines 60-65).

Consider **claim 4**, and **as applied to claim 1 above**, Rouffet et al discloses the claimed invention except for having 1 back up satellite.

However, Farrell discloses as known in the art discloses a replacement satellite (col. 9, lines 29-39).

Therefore, it would have been obvious of one of ordinary skill in the art to incorporate the teachings of Farrell into the system of Rouffet et al in order to provide a replacement satellite that can emulate the communications performance of geostationary communications satellites.

Consider **claim 5**, and as applied to **claim 1** above, Rouffet et al further disclose the claimed invention wherein the area comprises a plurality of zones, each having a peak demand at a different time period (figs. 1 and 2; col. 3, lines 5-20; Geostationary satellites S1 and S2 having two coverage areas T1 and T2 on two distinct accesses each being capable of subsequently retransmitting two distinct beams, wherein antenna 1 of satellite S1 retransmitting a beam F1 to the area T1 of the Earth, and a beam F2 to the area T2 of the Earth and antenna 2 of satellite S2 retransmitting a beam F'1 to the area T1, and a beam F'2 to the area T2).

Consider **claim 6**, and as applied to **claim 1** above, Rouffet et al further disclose the claimed invention wherein the satellite communication system facilitates data access by user terminals (col. 1, lines 10-15; Satellite telecommunications facility applies to the field of direct television broadcasting to a plurality of geographical coverage areas.).

Consider **claim 7**, Rouffet et al show and disclose a satellite communication system comprising  $m$  primary satellites, each equipped to project  $N/m$  beams onto and across an area in a loosely-packed array manner to collectively create  $N$  beam spots to cover the area, with each sub-area covered by a beam spot separated from another sub-area covered by another beam spot by one beam width,  $m$  being an integer greater than 1 (figs. 1 and 2; col. 3, lines 5-20; col. 4, lines 60-65; col. 5, lines 4-14; Geostationary satellites S1 and S2 having two coverage areas T1



Art Unit: 2618

and T2 on two distinct accesses each being capable of subsequently retransmitting two distinct beams, wherein antenna 1 of satellite S1 retransmitting a beam F1 to the area T1 of the Earth, and a beam F2 to the area T2 of the Earth and antenna 2 of satellite S2 retransmitting a beam F'1 to the area T1, and a beam F'2 to the area T2. A third satellite S3 identical to the satellites S1 and S2 already in orbit, which is fed with a wave E3 by a transmission antenna 21 on the Earth and is capable of retransmitting two beams F''1 and F''2 towards area T1 and T2. Furthermore, beam F1 will carry two transmission channels to area T1, beam F2 will carry three transmission channels to area T2, beam F'1 will carry three transmission channels to area T1, and beam F'2 will carry two transmission channels to area T2.).

Rouffet et al fail to disclose  $n$  back up satellites, each also equipped to project  $N/m$  beams onto and across the area in a loosely-packed array manner, with each sub-area covered by a beam spot separated from another sub-area covered by another beam spot by one beam width, to enable a selected one of the  $n$  back up satellites to replace any one of the  $m$  primary satellites on demand,  $n$  being an integer equal to or greater than 1.

However, Farrell shows and discloses as known in the art a universal replacement communications satellite designed for orbiting the Earth in a geostationary orbit which emulates the communications performance of a substantial percentage of existing geostationary communication satellites and therefore for which it can be a replacement (col. 3, lines 40-55). Furthermore, Farrell discloses that the replacement satellite comprises two or more Ku and 2 or more C band downlink antennas, each antenna capable of outputting a downlink beam comprising downlink Ku and C band signals, respectively, with each downlink beam being separately directable to different locations on Earth (col. 4, lines 14-19 and 33-37).

Therefore, it would have been obvious of one of ordinary skill in the art to incorporate the teachings of Farrell into the system of Rouffet et al to have a practical but satisfactory replacement satellite that can emulate the performance of the main or primary satellites while still being technologically, economically, and other practicable.

Consider **claim 8**, and as **applied to claim 7 above**, Rouffet et al further disclose 3 primary satellites (fig. 3; col. 4, lines 60-65).

Consider **claim 9**, and as **applied to claim 7 above**, Rouffet et al disclose the claimed invention except for having 1 back up satellite.

However, Farrell discloses as known in the art discloses a replacement satellite (col. 9, lines 29-39).

Therefore, it would have been obvious of one of ordinary skill in the art to incorporate the teachings of Farrell into the system of Rouffet et al in order to provide a replacement satellite that can emulate the communications performance of geostationary communications satellites.

Consider **claim 10**, and as **applied to claim 7 above**, Rouffet et al further disclose the claimed invention wherein the area comprises a plurality of zones, each having a peak demand at a different time period (figs. 1 and 2; col. 3, lines 5-20; Geostationary satellites S1 and S2 having two coverage areas T1 and T2 on two distinct accesses each being capable of subsequently retransmitting two distinct beams, wherein antenna 1 of satellite S1 retransmitting a beam F1 to the area T1 of the Earth, and a beam F2 to the area T2 of the Earth and antenna 2 of satellite S2 retransmitting a beam F'1 to the area T1, and a beam F'2 to the area T2).

Consider **claim 12**, Rouffet et al show and disclose a satellite communication system comprising  $m$  primary multi-beam satellites, each equipped to facilitate communication over 1 of

Art Unit: 2618

$m$  bands of frequencies on one beam,  $m$  being an integer greater than 1 (figs. 1 and 2; col. 3, lines 5-20; col. 4, lines 60-65; col. 5, lines 4-14; Geostationary satellites S1 and S2 having two coverage areas T1 and T2 on two distinct accesses each being capable of subsequently retransmitting two distinct beams, wherein antenna 1 of satellite S1 retransmitting a beam F1 to the area T1 of the Earth, and a beam F2 to the area T2 of the Earth and antenna 2 of satellite S2 retransmitting a beam F'1 to the area T1, and a beam F'2 to the area T2. A third satellite S3 identical to the satellites S1 and S2 already in orbit, which is fed with a wave E3 by a transmission antenna 21 on the Earth and is capable of retransmitting two beams F''1 and F''2 towards area T1 and T2. Furthermore, beam F1 will carry two transmission channels to area T1, beam F2 will carry three transmission channels to area T2, beam F'1 will carry three transmission channels to area T1, and beam F'2 will carry two transmission channels to area T2.).

Rouffet et al fail to disclose  $n$  back up multi-beam satellites, each equipped to facilitate communication over 1 of  $m$  bands of frequencies on one beam,  $n$  being an integer equal to or greater than 1.

However, Farrell shows and discloses as known in the art a universal replacement communications satellite designed for orbiting the Earth in a geostationary orbit which emulates the communications performance of a substantial percentage of existing geostationary communication satellites and therefore for which it can be a replacement (col. 3, lines 40-55). Furthermore, Farrell discloses that the replacement satellite comprises two or more Ku and 2 or more C band downlink antennas, each antenna capable of outputting a downlink beam comprising downlink Ku and C band signals, respectively, with each downlink beam being

Art Unit: 2618

separately directable to different locations on Earth (col. 4, lines 14-19 and 33-37). The replacement satellite will be designed for the same uplink and downlink frequency plans and telemetry and command subsystem frequencies (col. 2, lines 22-26).

Therefore, it would have been obvious of one of ordinary skill in the art to incorporate the teachings of Farrell into the system of Rouffet et al to have a practical but satisfactory replacement satellite that can emulate the performance of the main or primary satellites while still being technologically, economically, and other practicable.

Consider **claim 13**, and as **applied to claim 12 above**, Rouffet et al further disclose 3 primary multi-beam satellites (fig. 3; col. 4, lines 60-65).

Consider **claim 14**, and as **applied to claim 12 above**, Rouffet et al discloses the claimed invention except for having 1 back up multi-beam satellites.

However, Farrell discloses as known in the art discloses a replacement satellite (col. 9, lines 29-39).

Therefore, it would have been obvious of one of ordinary skill in the art to incorporate the teachings of Farrell into the system of Rouffet et al in order to provide a replacement satellite that can emulate the communications performance of geostationary communications satellites.

Consider **claim 18**, Rouffet et al show and disclose a satellite communication system comprising  $m$  primary satellites, each equipped to project  $N/m$  beams onto an area,  $m$  being an integer greater than 1 (figs. 1 and 2; col. 3, lines 5-20; col. 4, lines 60-65; Geostationary satellites S1 and S2 having two coverage areas T1 and T2 on two distinct accesses each being capable of subsequently retransmitting two distinct beams, wherein antenna 1 of satellite S1 retransmitting a beam F1 to the area T1 of the Earth, and a beam F2 to the area T2 of the Earth and antenna 2 of

satellite S2 retransmitting a beam F'1 to the area T1, and a beam F'2 to the area T2. A third satellite S3 identical to the satellites S1 and S2 already in orbit, which is fed with a wave E3 by a transmission antenna 21 on the Earth and is capable of retransmitting two beams F''1 and F''2 towards area T1 and T2.).

Rouffet et al fail to disclose  $n$  back up satellites, each equipped to project  $N/m$  beams onto the area, to enable a selected one of the  $n$  back up satellites to replace any one of the  $m$  primary satellites on demand,  $n$  being an integer equal to or greater than 1.

However, Farrell shows and discloses as known in the art a universal replacement communications satellite designed for orbiting the Earth in a geostationary orbit which emulates the communications performance of a substantial percentage of existing geostationary communication satellites and therefore for which it can be a replacement (col. 3, lines 40-55).

Therefore, it would have been obvious of one of ordinary skill in the art to incorporate the teachings of Farrell into the system of Rouffet et al to have a practical but satisfactory replacement satellite that can emulate the performance of the main or primary satellites while still being technologically, economically, and other practicable.

Consider **claim 19**, and as applied to **claim 18 above**, Rouffet et al further disclose 3 primary satellites (fig. 3; col. 4, lines 60-65).

Consider **claim 20**, and as applied to **claim 18 above**, Rouffet et al discloses the claimed invention except for having 1 back up satellite.

However, Farrell discloses as known in the art discloses a replacement satellite (col. 9, lines 29-39).

Therefore, it would have been obvious of one of ordinary skill in the art to incorporate the teachings of Farrell into the system of Rouffet et al in order to provide a replacement satellite that can emulate the communications performance of geostationary communications satellites.

Consider **claim 21**, and as applied to **claim 18 above**, Rouffet et al further disclose the claimed invention wherein the area comprises a plurality of zones, each having a peak demand at a different time period (figs. 1 and 2; col. 3, lines 5-20; Geostationary satellites S1 and S2 having two coverage areas T1 and T2 on two distinct accesses each being capable of subsequently retransmitting two distinct beams, wherein antenna 1 of satellite S1 retransmitting a beam F1 to the area T1 of the Earth, and a beam F2 to the area T2 of the Earth and antenna 2 of satellite S2 retransmitting a beam F'1 to the area T1, and a beam F'2 to the area T2).

Consider **claim 25**, and as applied to **claim 24 above**, Rouffet et al disclose the claimed invention except for the method comprising configuring on demand a selected one of  $n$  back up satellites to project  $N/m$  beams onto and across the area in a loosely-packed array manner, with each sub-area covered by a beam spot separated from another sub-area covered by another beam spot by one beam width, to replace one of the  $m$  primary satellites with the selected one of the  $n$  back up satellites,  $n$  being equal to or greater than 1. Furthermore, Rouffet et al fail to disclose configuring the selected one of the  $n$  back up satellites to facilitate communication over 1 of  $m$  band of frequencies on one beam, the 1 of  $m$  band of frequencies being the 1 of  $m$  band of frequencies previously employed by the replaced primary satellite,  $n$  being an integer equal to or greater than 1.

However, Farrell shows and discloses as known in the art a universal replacement communications satellite designed for orbiting the Earth in a geostationary orbit which emulates

Art Unit: 2618

the communications performance of a substantial percentage of existing geostationary communication satellites and therefore for which it can be a replacement (col. 3, lines 40-55). Furthermore, Farrell discloses that the replacement satellite comprises two or more Ku and 2 or more C band downlink antennas, each antenna capable of outputting a downlink beam comprising downlink Ku and C band signals, respectively, with each downlink beam being separately directable to different locations on Earth (col. 4, lines 14-19 and 33-37). The replacement satellite will be designed for the same uplink and downlink frequency plans and telemetry and command subsystem frequencies (col. 2, lines 22-26).

Therefore, it would have been obvious of one of ordinary skill in the art to incorporate the teachings of Farrell into the system of Rouffet et al to have a practical but satisfactory replacement satellite that can emulate the performance of the main or primary satellites while still being technologically, economically, and other practicable.

Consider **claim 26**, Rouffet et al disclose a method comprising configuring each of  $m$  primary multi-beam satellites to facilitate communication over 1 of  $m$  band of frequencies on each beam,  $m$  being greater than 1 (figs. 1 and 2; col. 3, lines 5-20; col. 4, lines 60-65; col. 5, lines 4-14; Geostationary satellites S1 and S2 having two coverage areas T1 and T2 on two distinct accesses each being capable of subsequently retransmitting two distinct beams, wherein antenna 1 of satellite S1 retransmitting a beam F1 to the area T1 of the Earth, and a beam F2 to the area T2 of the Earth and antenna 2 of satellite S2 retransmitting a beam F'1 to the area T1, and a beam F'2 to the area T2. A third satellite S3 identical to the satellites S1 and S2 already in orbit, which is fed with a wave E3 by a transmission antenna 21 on the Earth and is capable of retransmitting two beams F''1 and F''2 towards area T1 and T2. Furthermore, beam F1 will carry

Art Unit: 2618

two transmission channels to area T1, beam F2 will carry three transmission channels to area T2, beam F'1 will carry three transmission channels to area T1, and beam F'2 will carry two transmission channels to area T2.).

Rouffet et al fail to disclose configuring a selected one of  $n$  back up multi-beam satellites to facilitate communication over 1 of  $m$  band of frequencies on each beam, the 1 of  $m$  band of frequencies being the 1 of  $m$  band of frequencies previously employed by the replaced primary multi-beam satellite,  $n$  being an integer equal to or greater than 1.

However, Farrell shows and discloses as known in the art a universal replacement communications satellite designed for orbiting the Earth in a geostationary orbit which emulates the communications performance of a substantial percentage of existing geostationary communication satellites and therefore for which it can be a replacement (col. 3, lines 40-55). Furthermore, Farrell discloses that the replacement satellite comprises two or more Ku and 2 or more C band downlink antennas, each antenna capable of outputting a downlink beam comprising downlink Ku and C band signals, respectively, with each downlink beam being separately directable to different locations on Earth (col. 4, lines 14-19 and 33-37). The replacement satellite will be designed for the same uplink and downlink frequency plans and telemetry and command subsystem frequencies (col. 2, lines 22-26).

Therefore, it would have been obvious of one of ordinary skill in the art to incorporate the teachings of Farrell into the system of Rouffet et al to have a practical but satisfactory replacement satellite that can emulate the performance of the main or primary satellites while still being technologically, economically, and other practicable.



Consider **claim 27**, Rouffet et show and disclose a method of configuring  $m$  primary satellites to project  $N/m$  beams onto and across an area (figs. 1 and 2; col. 3, lines 5-20; col. 4, lines 60-65; Geostationary satellites S1 and S2 having two coverage areas T1 and T2 on two distinct accesses each being capable of subsequently retransmitting two distinct beams, wherein antenna 1 of satellite S1 retransmitting a beam F1 to the area T1 of the Earth, and a beam F2 to the area T2 of the Earth and antenna 2 of satellite S2 retransmitting a beam F'1 to the area T1, and a beam F'2 to the area T2. A third satellite S3 identical to the satellites S1 and S2 already in orbit, which is fed with a wave E3 by a transmission antenna 21 on the Earth and is capable of retransmitting two beams F''1 and F''2 towards area T1 and T2.).

Rouffet et al fail to disclose configuring on demand a selected one of  $n$  back up satellites to project  $N/m$  beams onto and across the area coincidence with one of the  $m$  primary satellites is configured to project its  $N/m$  beams onto and across an area, to replace the one primary satellite with the selected one of the  $n$  back up satellites,  $n$  being equal to or greater than 1.

However, Farrell shows and discloses as known in the art a universal replacement communications satellite designed for orbiting the Earth in a geostationary orbit which emulates the communications performance of a substantial percentage of existing geostationary communication satellites and therefore for which it can be a replacement (col. 3, lines 40-55).

Therefore, it would have been obvious of one of ordinary skill in the art to incorporate the teachings of Farrell into the system of Rouffet et al to have a practical but satisfactory replacement satellite that can emulate the performance of the main or primary satellites while still being technologically, economically, and other practicable.

Consider **claim 28**, Rouffet et show and disclose a gateway for communicating signals through a satellite communication system comprising means for transferring signals through  $m$  primary satellites, each equipped to project  $N/m$  beams onto an area,  $m$  being an integer greater than 1 (figs. 1 and 2; col. 3, lines 5-20; col. 4, lines 60-65; Geostationary satellites S1 and S2 having two coverage areas T1 and T2 on two distinct accesses each being capable of subsequently retransmitting two distinct beams, wherein antenna 1 of satellite S1 retransmitting a beam F1 to the area T1 of the Earth, and a beam F2 to the area T2 of the Earth and antenna 2 of satellite S2 retransmitting a beam F'1 to the area T1, and a beam F'2 to the area T2. A third satellite S3 identical to the satellites S1 and S2 already in orbit, which is fed with a wave E3 by a transmission antenna 21 on the Earth and is capable of retransmitting two beams F''1 and F''2 towards area T1 and T2.).

Rouffet et al fail to disclose a gateway for communicating signals through a satellite communication system comprising means for transferring signals through  $n$  back up satellites, each equipped to project  $N/m$  beams onto the area, to enable a selected one of the  $n$  back up satellites to replace any one of the  $m$  primary satellites on demand,  $n$  being an integer equal to or greater than 1.

However, Farrell shows and discloses as known in the art a universal replacement communications satellite designed for orbiting the Earth in a geostationary orbit which emulates the communications performance of a substantial percentage of existing geostationary communication satellites and therefore for which it can be a replacement (col. 3, lines 40-55).

Therefore, it would have been obvious of one of ordinary skill in the art to incorporate the teachings of Farrell into the system of Rouffet et al to have a practical but satisfactory

Art Unit: 2618

replacement satellite that can emulate the performance of the main or primary satellites while still being technologically, economically, and other practicable.

Consider **claim 29**, Rouffet et show and disclose a user terminal for communicating signals through a satellite communication system to at least one gateway comprising means for transferring signals through  $m$  primary satellites, each equipped to project  $N/m$  beams onto an area,  $m$  being an integer greater than 1 (figs. 1 and 2; col. 3, lines 5-20; col. 4, lines 60-65; Geostationary satellites S1 and S2 having two coverage areas T1 and T2 on two distinct accesses each being capable of subsequently retransmitting two distinct beams, wherein antenna 1 of satellite S1 retransmitting a beam F1 to the area T1 of the Earth, and a beam F2 to the area T2 of the Earth and antenna 2 of satellite S2 retransmitting a beam F'1 to the area T1, and a beam F'2 to the area T2. A third satellite S3 identical to the satellites S1 and S2 already in orbit, which is fed with a wave E3 by a transmission antenna 21 on the Earth and is capable of retransmitting two beams F''1 and F''2 towards area T1 and T2.).

Rouffet et al fail to disclose a user terminal for communicating signals through a satellite communication system to at least one gateway comprising means for transferring signals through  $n$  back up satellites, each equipped to project  $N/m$  beams onto the area, to enable a selected one of the  $n$  back up satellites to replace any one of the  $m$  primary satellites on demand,  $n$  being an integer equal to or greater than 1.

However, Farrell shows and discloses as known in the art a universal replacement communications satellite designed for orbiting the Earth in a geostationary orbit which emulates the communications performance of a substantial percentage of existing geostationary communication satellites and therefore for which it can be a replacement (col. 3, lines 40-55).

Therefore, it would have been obvious of one of ordinary skill in the art to incorporate the teachings of Farrell into the system of Rouffet et al to have a practical but satisfactory replacement satellite that can emulate the performance of the main or primary satellites while still being technologically, economically, and other practicable.

Consider **claim 30**, Rouffet et show and disclose an apparatus for use in a satellite communication system comprising means for configuring  $m$  primary multi-beam satellites to project  $N/m$  beams onto an area to collectively create  $N$  beam spots to cover the area, with  $m$  being an integer greater than 1 (figs. 1 and 2; col. 3, lines 5-20; col. 4, lines 60-65; Geostationary satellites S1 and S2 having two coverage areas T1 and T2 on two distinct accesses each being capable of subsequently retransmitting two distinct beams, wherein antenna 1 of satellite S1 retransmitting a beam F1 to the area T1 of the Earth, and a beam F2 to the area T2 of the Earth and antenna 2 of satellite S2 retransmitting a beam F'1 to the area T1, and a beam F'2 to the area T2. A third satellite S3 identical to the satellites S1 and S2 already in orbit, which is fed with a wave E3 by a transmission antenna 21 on the Earth and is capable of retransmitting two beams F''1 and F''2 towards area T1 and T2.).

Rouffet et al fail to disclose an apparatus for use in a satellite communication system comprising means for configuring a selected one of  $n$  back up multi-beam satellites to project  $N/m$  beams onto the area, to replace one primary satellite with the selected one of the  $n$  back up satellites,  $n$  being equal to or greater than 1.

However, Farrell shows and discloses as known in the art a universal replacement communications satellite designed for orbiting the Earth in a geostationary orbit which emulates

the communications performance of a substantial percentage of existing geostationary communication satellites and therefore for which it can be a replacement (col. 3, lines 40-55).

Therefore, it would have been obvious of one of ordinary skill in the art to incorporate the teachings of Farrell into the system of Rouffet et al to have a practical but satisfactory replacement satellite that can emulate the performance of the main or primary satellites while still being technologically, economically, and other practicable.

7. **Claims 11, 15, and 16 are rejected under 35 U.S.C. 103(a) as being unpatentable over Rouffet et al (United States Patent #5,410,731) in view of Farrell (European Patent Application EP 1 065 806 A2) in further view of Faineant et al (United States Patent Application Publication #2002/0089943 A1).**

Consider **claim 11**, and as **applied to claim 7 above**, Rouffet et al, as modified by Farrell, further modified by Faineant et al, show and disclose the claimed invention except for wherein the satellite communication system facilitate Internet access by user terminals.

However, Faineant et al show and disclose two satellite terminals connected to user terminals, a satellite and an Internet service provider (fig. 4, paragraph 74).

Therefore, it would have been obvious of one of ordinary skill in the art to incorporate the teachings of Faineant et al into the system of Rouffet et al in order for users to be able to send information via the Internet through satellite communications.

Consider **claim 15**, and as **applied to claim 12 above**, Rouffet et al, as modified by Farrell, further modified by Faineant et al, show and disclose the claimed invention except for

wherein the satellite communication system facilitate access by user terminals to a communication network.

However, Faineant et al show and disclose two satellite terminals connected to user terminals, a satellite and an Internet service provider (fig. 4, paragraph 74).

Therefore, it would have been obvious of one of ordinary skill in the art to incorporate the teachings of Faineant et al into the system of Rouffet et al in order for users to be able to send information via the Internet through satellite communications.

Consider **claim 16**, and as **applied to claim 15 above**, Rouffet et al, as modified by Farrell, further modified by Faineant et al, show and disclose the claimed invention except for wherein the satellite communication system comprises the Internet.

However, Faineant et al show and disclose two satellite terminals connected to user terminals, a satellite and an Internet service provider (fig. 4, paragraph 74).

Therefore, it would have been obvious of one of ordinary skill in the art to incorporate the teachings of Faineant et al into the system of Rouffet et al in order for users to be able to send information via the Internet through satellite communications.

8. **Claim 17** is rejected under 35 U.S.C. 103(a) as being unpatentable over **Rouffet et al (United States Patent #5,410,731)** in view of **Farrell (European Patent Application EP 1 065 806 A2)** in further view of **Faineant et al (United States Patent Application Publication #2002/0089943 A1)** in further view of **Stetson et al (United States Patent Application Publication #2002/0169669 A1)**.

Consider **claim 17**, and as **applied to claim 15 above**, Rouffet et al, in view of Farrell, as modified by Farrell, further modified by Faineant et al, show and disclose the claimed invention except for wherein the communications network comprises an enterprise Intranet.

However, Stetson et al show and disclose connections between user devices that include intranets and satellite links or networks (paragraph 115).

Therefore, it would have been obvious to one of ordinary skill in the art to incorporate the teachings of Stetson et al into the system of Rouffet et al in order for users to be able to send information via the Intranet through satellite links or networks.

9. **Claim 22** is rejected under 35 U.S.C. 103(a) as being unpatentable over **Rouffet et al (United States Patent #5,410,731)** in view of **Chandler (United States Patent #6,219,003 B1)**.

Consider **claim 22**, Rouffet et al disclose a satellite communication system that projects N/m beams onto an area in a loosely-packed array manner, to contribute to covering N/m sub-areas of the area with m-1 other satellites, with each sub-area covered by a beam spot separated from another sub-area covered by another beam spot by one beam width. (figs. 1 and 2; col. 3, lines 5-20; col. 4, lines 60-65; col. 5, lines 4-14; Geostationary satellites S1 and S2 having two coverage areas T1 and T2 on two distinct accesses each being capable of subsequently retransmitting two distinct beams, wherein antenna 1 of satellite S1 retransmitting a beam F1 to the area T1 of the Earth, and a beam F2 to the area T2 of the Earth and antenna 2 of satellite S2 retransmitting a beam F'1 to the area T1, and a beam F'2 to the area T2. A third satellite S3 identical to the satellites S1 and S2 already in orbit, which is fed with a wave E3 by a transmission antenna 21 on the Earth and is capable of retransmitting two beams F''1 and F''2

Art Unit: 2618

towards area T1 and T2. Furthermore, beam F1 will carry two transmission channels to area T1, beam F2 will carry three transmission channels to area T2, beam F'1 will carry three transmission channels to area T1, and beam F'2 will carry two transmission channels to area T2.).

Rouffet et al fail to disclose that the satellite comprises at least one transponder and an antenna system having a reflector and  $N/m$  feed horns, coupled to the transponder.

However, Chandler discloses as known in the art a that modern cellular communications employ satellite based links for relaying signals between different Earth based stations, wherein the satellite contains RF transponder systems that are capable of receiving and relaying signals from many different stations on Earth to other stations. A key component in that transponder system is the microwave transmitting (or receiving) antenna, which is a reflector antenna. A reflector antenna employs a microwave feed horn and a parabolic reflector. (col. 1, lines 11-26)

Therefore, it would have been obvious to one of ordinary skill in the art to incorporate the teachings of Chandler into the system of Rouffet et al to be able to efficiently communicate to an area on Earth.

Consider **claim 23**, and as applied to **claim 22 above**, Rouffet et al further disclose the claimed invention wherein the area comprises a plurality of zones, each having a peak demand at a different time period (figs. 1 and 2; col. 3, lines 5-20; Geostationary satellites S1 and S2 having two coverage areas T1 and T2 on two distinct accesses each being capable of subsequently retransmitting two distinct beams, wherein antenna 1 of satellite S1 retransmitting a beam F1 to the area T1 of the Earth, and a beam F2 to the area T2 of the Earth and antenna 2 of satellite S2 retransmitting a beam F'1 to the area T1, and a beam F'2 to the area T2).



*Conclusion*

10. Anzel (U.S. Patent # 5,020,746) disclose **Method for satellite station keeping.**  
Pocha et al (U.S. Patent # 5,120,007) disclose **Geostationary satellite system.**  
Berkowitz (U.S. Patent # 5,175,556) disclose **Spacecraft antenna pattern control system.**  
Lenormand et al (U.S. Patent # 5,289,193) disclose **Reconfigurable transmission antenna.**  
Takahashi et al (U.S. Patent # 5,297,134) disclose **Loop mode transmission system with bus mode backup.**  
Mueller et al (U.S. Patent # 5,323,322) disclose **Networked differential GPS system.**  
Cances et al (U.S. Patent # 5,355,138) disclose **Antenna beam coverage reconfiguration.**  
Bishop (U.S. Patent # 5,523,997) disclose **Communication network with dynamic intraswitching.**  
Sabourin et al (U.S. Patent # 5,563,880) disclose **Methods for managing and distributing payload instructions.**  
Pizzicaroli et al (U.S. Patent # 5,813,634) disclose **Method for replacing failing satellites in a satellite communication system.**  
Pond (U.S. Patent # 5,860,056) disclose **Satellite information update system.**  
Chethik (U.S. Patent # 5,890,679) disclose **Medium earth orbit communication satellite system.**

Art Unit: 2618

Bond (U.S. Patent # 3,995,801) disclose **Method of storing spare satellites in orbit.**

Dondl (U.S. Patent # 4,502,051) disclose **Telecommunication system with satellites positioned in geostationary positional loops.**

Edridge (U.S. Patent # 4,688,259) disclose **Reconfigurable multiplexer.**

deSantis (U.S. Patent # 4,858,225) disclose **Variable bandwidth variable center-frequency multibeam satellite-switched router.**

Lenormand et al (U.S. Patent # 4,965,587) disclose **Antenna which is electronically reconfigurable in transmission.**

Dixon et al (EP 1014598 B1) disclose **Reconfigurable satellite for modifying predetermined characteristics of payload, with flexible antenna system and agile repeater for handling various uplink and downlink frequency plans.**

11. Any response to this Office Action should be **faxed to (571) 273-8300 or mailed to:**

Commissioner for Patents  
P.O. Box 1450  
Alexandria, VA 22313-1450

**Hand-delivered responses** should be brought to

Customer Service Window  
Randolph Building  
401 Dulany Street  
Alexandria, VA 22314

Any inquiry concerning this communication or earlier communications from the Examiner should be directed to Bobbak Safaipour whose telephone number is (571) 270-1092. The Examiner can normally be reached on Monday-Friday from 9:00am to 5:00pm.

If attempts to reach the Examiner by telephone are unsuccessful, the Examiner's supervisor, Edan Orgad can be reached on (571) 272-7884. The fax phone number for the organization where this application or proceeding is assigned is (571) 273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free) or 703-305-3028.

Any inquiry of a general nature or relating to the status of this application or proceeding should be directed to the receptionist/customer service whose telephone number is (571) 272-2600.

*Bobbak Safaipour*  
B.S./bs

October 16, 2006

EDAN ORGAD  
PATENT EXAMINER/TELECOMM.

*Edan Orgad* 10/16/06